

It's so **SMART**... it makes cents.
SMARTANK™

SINGLE TANK APPLICATIONS



SMARTank is a completely wireless tank level monitoring system **designed to provide** petroleum distributors with the ultimate in **flexibility** and **performance**. SMARTank monitors require no external power, telephone lines or restrictive AC powered controllers. Its unique features and **simple installation** put the SMARTank system in a class of its own.

To get information about our 30-day money back guarantee evaluation program, call us today at 803-547-8265 or visit our Web site at www.smartlogixinc.com.



SINGLE TANK APPLICATIONS



The SMARTank "Prophet" Tank monitor has been designed for single tank applications where either an Analog or Digital (GSM) cellular network is available. The "Prophet" can be configured for virtually any height tank and is ideal for above ground stationary or portable diesel, lube or gasoline applications.

Comparison of 1000 Gallon Tanks				
SMARTANK				
800	\$45.00	\$0.15	\$0.06	<i>More than Double!</i> \$0.09
Average Delivery Volume	Average Delivery Cost	Average Fuel Margin	Cost of Delivery per Gallon	Net Profit per Gallon Delivered
Un-Smart				
400	\$45.00	\$0.15	\$0.11	\$0.04
Average Delivery Volume	Average Delivery Cost	Average Fuel Margin	Cost of Delivery per Gallon	Net Profit per Gallon Delivered

BENEFITS:

- > Increased Delivery Efficiency
- > Expanded Marketing Areas
- > Increased Margins
- > Increased Fleet Capacity
- > Provides True Differentiation
- > Increased Sales Opportunities

SMARTank Also:

- > Decreases Number of Invoices
- > Eliminates Emergency Deliveries
- > Improves Customer Satisfaction

HOW IT WORKS

SMARTank's single tank monitors are battery powered completely wireless devices that use cellular communication and either a differential pressure sensor or magnetic float to measure tank levels and transmit data to the SMARTank data center. Monitors can be programmed remotely to report tank levels at a specific time, at predetermined intervals or when a significant change in tank volume is detected.

Distributors and their customers can access tank level information via SMARTank's web site using unique user I.D. and passwords. Passwords are assigned at the tank level providing distributors with ultimate flexibility to control customer access to information.

Installation:

From the beginning, the hallmark of SMARTank's success has been our unwavering commitment to customer support. For most customers, that means playing little or no role in the tank set-up on the web site. A driver simply drops the sensor into the tank and calls SMARTank's Customer Service. A SMARTank representative records new customer information, instructs the installer to initialize the monitor and then stays on the phone until the reported tank level is verified and set up is complete.

Reporting:

The SMARTank web site allows you to generate customized web based reports, download to an Excel spreadsheet or import tank level information to SMARTank's Digital Dispatch & Delivery Software. In addition to tank level information, the SMARTank web site provides:

- > Battery Life & Signal Strength
- > Territory, Route, & Product Reporting
- > Alarm Status
- > Product Usage
- > Fill History

Dispatch & Deliveries:

SMARTank's web application has been designed to fully integrate with SMARTruck's™ Digital Dispatch & Delivery Software. Tanks flagged as "low" or "critically low" on the SMARTank web site are automatically downloaded into the SMARTruck's dispatch module for review and assignment to delivery vehicles.

